MR-Q3-600LE-D(HI)

Autonomous Mobile Robot



Key Feature

- Self-localization navigation: adopts inertial, 2D barcode, laser and visual SLAM navigation methods to achieve accurate positioning.
- Supports smooth motions like forward, backward, and rotation via dual-wheel differential drive.
- Smart power management: supports multi-level electrical threshold, auto-charging, and self-returning after charging completed.
- Multi-safety protection: includes front laser obstacle avoidance, side ultrasonic obstacle avoidance, bumper strip detection, emergency stop button, etc.
- Human-machine interaction: indicates the device status via touch screen, sound and indicators.
- Supports lifting, carrying, rotating and lowering goods up to 600 kg (1322.77 lb.).
- Wireless communication: supports Wi-Fi and seamless roaming in a network covered area.

Typical Application

Automobile, 3C, manufacturing, logistics, food, medicine, etc.


Available Model

MR-Q3-600LE-D(HI)

Accessory


Charging station model: MR-RA-CH-48/30B-CI(CE)

Dimension



Unit: mm

Charging Station Deployment



Specification

Model			MR-Q3-600LE-D(HI)
Basic Parameter			
Dimension (L × W × H)			950 mm × 650 mm × 250mm (37.40" × 25.59" × 9.84")
Rotation Diameter			995 mm (39.17")
Chassis Above Ground			25 mm (0.98")
Distance Above Ground from Charging Port			130 mm (5.12")
Charging Distance			572 mm (22.52")
Lifting Platform Dimension			850 mm × 600 mm (33.46" × 23.62")
Lifting Stroke			60 mm (2.36")
Lifting Structure Type			Electric
Weight			128 kg (282.19 lb.)
Rated Load			600 kg (1322.77 lb.)
Navigation Mode			Laser SLAM/2D barcode/Visual SLAM (ground texture)
Human-Machine Interaction			Touch screen
Safety Protection			
Front	**Laser Obstacle Avoidance**	**Installation Height**	190 mm (7.48")
		Scanning Angle	260°
		Max. Detection Range	10 m (393.70")
Bumper Strip Type			Mechanical
Emergency Stop Button			Support
Motion Performance			
Rated Running Speed (Empty)			2000 mm/s
Rated Running Speed (Rated Load)			1800 mm/s
Rated Acceleration (Empty)			1000 mm/s²
Rated Acceleration (Rated Load)			500 mm/s²
Rotation Speed (Empty)			200°/s
Rotation Speed (Rated Load)			100°/s
Gradeability			3°
Location Angle Accuracy			± 1°
Location Accuracy			± 10 mm (± 0.39")
Battery Performance			
Battery Type			LiFePO4
Rated Voltage			48 V
Charging Cycle			1500 times (for fully charging and discharging) or 30 months
Run Time			6 h to 8 h
Charging Time			≤ 1.5 h (for fully charging and discharging)

Hangzhou Hikrobot Co. Ltd.
en.hikrobotics.com

© Hangzhou Hikrobot Co., Ltd. All Rights Reserved.
Hangzhou Hikrobot does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.