IP Network Amplifier

# T-78120W



## Product Introduction

Suitable for schools, office buildings, conference centers, parks, stations and other places. Adopt network digital transmission, achieve the functions of background music, timed ringing task, collecting sound source, one-way paging and other functions set in the system.

## Features

* Outdoor Wall-mounted design, small size, exquisite and beautiful.
* The device is designed with embedded computer technology and DSP audio processing technology; adopt high-speed industrial grade chip.
* Built-in network IP decoding module which can play network music and one-way paging function in real time; network delay time of collecting and one-way paging function in the system is less than 100ms.
* Built-in 1 x 120W constant voltage digital amplifier, less heat and higher efficiency.
* Compatible with any network structure such as router, switch, bridge gateway, Modem, Internet, 3G, 4G, etc.

## Product description

| | |
|---|---|
| Model | T-78120W |
| Network Interface | Standard RJ45 input |
| Support Protocol | TCP/IP, UDP |
| Audio Format | MP3 |
| Sampling Rate | 8K～48KHz |
| Transmission Rate | 100Mbps |
| Audio Mode | 16-bit CD sound quality |
| Total chopping distortion | ≤1% |
| Frequency Response | 80Hz～16KHz +1/- 3dB |
| S/N Ratio | ≥68dB |
| Working Temperature | -35℃～60℃ |
| Working Humidity | 20% to 80% Relative Humidity |
| Overall Power Consumption | ≤150W |
| Input Power | ～190-240V 50-60Hz |
| Dimensions | 189×110×40mm |

