DS-KEB08-LC
Lane Board



- Lane control board kit for barrier products. (actual corresponding barrier model refer to product model names).
- With fire input for linkage emergency door opening.

▪ Specification

Interface	
Exit button	0
Alarm output	0
RS-485	2
USB	0
Fire alarm input	1
Case input	1
General	
Power consumption	Standby: 50 W Working: 150 W Peak: 200 W
Working temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Working humidity	10% to 95% (No condensing)
Dimensions	Without package: 150 mm × 115.5 mm × 30 mm (5.91" × 4.56" × 1.18")
Weight	0.2Kg (0.41lb)
Power supply method	24V DC

▪ Available Model

DS-KEB08-LC/K3BM61X
DS-KEB08-LC/K6B411TX
DS-KEB08-LC/K6B630TX
DS-KEB08-LC/K6B961TX
DS-KEB08-LC/K6B530TX
DS-KEB08-LC/K6Y220TX
DS-KEB08-LC/K6BC402TX
DS-KEB08-LC/K6B530TX/Modular

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®