DS-2XE2601-1(CS)
Explosion Proof Flexible Conduit



- The main materials are braided line, carbon steel, and NBR.Connector is made by Carbon Steel.
- Suitable for cable protection in explosion-proof scenarios.
- II 2 G II 2 D Ex eb IIC Gb Ex tb IIIC Db


▪ Specification

General	
Material	Cover: PTFE, main body: Q235 ,Connector Material: Carbon steel
Dimension	Ø25 mm × 1000 mm . Thread Specification: G-3/4 Female and Male threads on two Sides
Weight	Approx 1.2kg
Startup and Operating Conditions	-40 °C to 60 °C . Humidity 95% or less (non-condensing)
Approval	
Protection	IP68 (2m/2h)
Explosion-proof sign	IECEx DNV 24.0038U Ex eb IIC Gb Ex tb IIIC Db DNV 24 ATEX 82754U II 2 G Ex eb IIC Gb II 2 D Ex tb IIIC Db

▪ Available Model

DS-2XE2601-1(CS)

▪ Dimension



See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®